Code: CE3T6

II B. Tech - I Semester – Regular Examinations - December 2014

FLUID MECHANICS (CIVIL ENGINEERING)

Duration: 3 hours Marks: 5x14=70

Answer any FIVE questions. All questions carry equal marks

- 1. a) Define
 - i) Specific Gravity
- ii) Viscosity
- iii) Surface Tension
- iv) Vapor Pressure

8 M

- b) An inverted differential manometer containing a fluid of specific gravity 0.8 is connected to find the difference of pressures at two points of a pipe containing water. If the manometer reading is 30 cm, find the difference of pressures.
- 2. a) For a vertical plane surface submerged in a liquid, derive expressions for 10 M
 - i) Total pressure, and
 - ii) Center of pressure
 - b) Write briefly about the hydrostatic forces acting on submerged bodies.

 4 M

| 3. a) Define: | | |
|-----------------------------|--|-------------|
| i) Stream line | ii) Path line | |
| iii) Streak lines | iv) Stream Tube | 8 M |
| b) What are various types | of flows? Explain. | 6 M |
| 4. Write about the signific | ance and applications of | • |
| i) Navier Stoke's | Equations | |
| ii) Euler's Equation | ns | |
| iii) Bernoulli's Eq | uation | |
| iv) Momentum Ec | uation by aptly stating t | he |
| equations. | | 14 M |
| 5. a) Define | | 4 M |
| i) Drag | | |
| ii) Lift | | |
| b) A flat plate 3m x 3m m | oves at 50 kmph in stati | ionary air |
| stream of density 1.25 | kg/m ³ . If the coefficient | of drag and |
| lift are 0.3 and 0.75 res | pectively, find | 10 M |
| i) the lift force | | |
| ii) the drag force | | |
| iii) the resultant for | orce | |
| iv) Angle made by | y the resultant force with | the plate |
| v) the power requi | ired to keep the plate in | motion. |

6. a) Write about the significance of Reynolds experiment. 6 M

- b) What are laminar and turbulent flows? Describe their characteristics with neat diagrams.

 8 M
- 7. a) Three pipes of lengths 600 m, 700m and 400m and diameters 200 mm, 300 mm and 100 mm are connected in series. Find the diameter of the equivalent pipe, if the 600m length pipe is replaced by 1000 m pipe of 250 mm Diameter. What is the percentage change in the diameter of the equivalent pipe? What is your inference?
 - b) Define:
 - i) Total Energy Line
 - ii) Hydraulic Gradient Line
- 8. a) Define an orifice-meter. When do you prefer orifice-meter to venturimeter?
 - b) Write about flow over
 - i) Rectangular Notch
 - ii) Triangular Notch
 - iii) Trapezoidal Notch
 - iv) Stepped Notch.

In case of low flows, which type of notch is used? Why?

8 M